

ITEM 619.53----25 – RELOCATE TEMPORARY CONCRETE BARRIER - TO REMAIN

1. DESCRIPTION:

- 1.01 The work shall consist of furnishing new (unused) Temporary Concrete Barrier or Temporary Concrete Barrier reset from the traffic control from this project in accordance with the specifications, the standard sheet and the lines and grades and locations shown on the plans or as established by the Engineer. The Temporary Concrete Barrier shall remain in place after completion of the contract. Ownership being transferred to the Authority by the Contractor.

2. MATERIALS:

- 2.01 The barrier shall be fabricated in accordance with Section 704-05, Precast Concrete Median Barrier and all details shown on the appropriate Standard Sheet. The connection keys and hardware shall be galvanized.
- 2.02 Any modification requested in the proportioning, air content, slump and curing shall be submitted to the Engineer for approval.

3. CONSTRUCTION DETAILS:

- 3.01 The Contractor shall furnish, deliver, and set the barrier at locations shown in the plans after any site preparation work has been completed. The barrier shall be maintained by the Contractor until the completion of the project and then left in place with ownership transferred to the Authority.

4. METHOD OF MEASUREMENT

- 4.01 The barrier shall be measured by the linear foot.

5. BASIS OF PAYMENT

- 5.01 The price bid per linear foot shall include the cost of all labor, equipment, connection keys, delineators and material necessary to furnish, install and maintain the barrier to project completion.