

**ITEM 502.50----25 - SAW CUTTING ASPHALT CONCRETE (FULL DEPTH)**

**1. DESCRIPTION:**

- 1.01 Under this item the Contractor shall saw cut asphalt concrete pavement in accordance with the plans and the directions of the Engineer.

**2. MATERIALS:**

- 2.01 Not Specified.

**3. CONSTRUCTION DETAILS:**

- 3.01 The saw cut shall be straight and parallel with joints in the adjacent slabs. The location of all saw cuts shall be made by the Engineer.
- 3.02 Extreme care shall be taken in sawing so as not to damage underlying concrete which is to remain. It shall be the responsibility of the Contractor to repair all damage caused by his operations at no cost to the Authority and to the satisfaction of the Engineer. The Contractor is advised that the thickness of the existing asphalt concrete overlay as shown on the plans is approximate only and is based on the best information available at the present time. The saw cut shall be made full depth of asphalt overlay. No additional compensation will be made for thickness more than, or less than, that shown on the plans.

**4. METHOD OF MEASUREMENT:**

- 4.01 The quantity to be paid for under this item will be the number of linear feet of saw cut incorporated in the work in accordance with the plans and as directed by the Engineer.

**5. BASIS OF PAYMENT:**

- 5.01 The unit price bid per linear foot shall include the cost of all labor, materials and equipment necessary to complete the work.