

ITEM 654.5110--25 - REUSABLE IMPACT ATTENUATOR, TL 2, ≤ 2 FT OBSTRUCTION WIDTH
ITEM 654.5111--25 - REUSABLE IMPACT ATTENUATOR, TL 2 > 2 FT UP TO 5 FT OBSTRUCTION WIDTH
ITEM 654.5112--25 - REUSABLE IMPACT ATTENUATOR, TL 2, >5 FT OBSTRUCTION WIDTH
ITEM 654.5120--25 - REUSABLE IMPACT ATTENUATOR, TL 3, ≤ 2 FT OBSTRUCTION WIDTH
ITEM 654.5121--25 - REUSABLE IMPACT ATTENUATOR, TL 3, > 2 FT UP TO 5 FT OBSTRUCTION WIDTH
ITEM 654.5122--25 - REUSABLE IMPACT ATTENUATOR, TL 3 >5 FT OBSTRUCTION WIDTH

All provisions of Section 654 pertaining to Reusable Impact Attenuators shall apply except as follows:

1. Under 654-2 Materials, **DELETE** reference to Subsection 712-08, Reusable Impact Attenuator.
2. Under 654-2 Materials, **INSERT** the following:
 - A. Only the following Reusable Impact Attenuators – Test Level 2 have been approved for use on the NYS Thruway.

PRODUCT	MANUFACTURER/SUPPLIER	RESTRICTIONS
SCI – 70GM	SCI Products, Inc. Harrisburg, PA	--

- B. Only the following Reusable Impact Attenuators – Test Level 3 have been approved for use on the NYS Thruway.

PRODUCT	MANUFACTURER/SUPPLIER	RESTRICTIONS
SCI-100GM	SCI Products, Inc. Harrisburg, PA	--