

ITEM 640.24XX--25 - REFLECTORIZED PAVEMENT MARKING PAINTS, 6 INCH WIDTH

1. DESCRIPTION:

- 1.01 Under this work the Contractor shall furnish and apply painted reflectorized pavement marking paint in accordance with these specifications, the Contract Documents, the Manual on Uniform Traffic Control Devices (MUTCD), or as ordered by the Engineer.
- 1.02 The marking material shall be applied by spray methods onto bituminous and Portland cement concrete pavement surfaces at the thickness and width shown on the Contract Documents and/or as indicated by the Pay Item Number.
- 1.03 The REFLECTORIZED PAVEMENT MARKING, SIX (6) INCH WIDTH Work Item shown in the plans will be the appropriate Item number for stripe color and application at a 15 ± 1 mil wet thickness.

ALL PROVISIONS OF SECTION 640 - REFLECTORIZED PAVEMENT MARKING PAINTS SHALL APPLY EXCEPT AS MODIFIED BELOW:

4. METHOD OF MEASUREMENT:

- 4.01 Shall be as in Section 640 except:

Pavement striping will be measured in linear feet along the centerline of the pavement stripe, and will be based on a six (6) inch wide stripe. Measurements for striping with a width greater or lesser than the basic six (6) inches, as shown on the plans or directed by the Engineer, will be made by calculating payment length using the following method:

Plan Width of Striping (inches) X Linear Feet Measured
6 Inches

5. BASIS OF PAYMENT:

- 5.01 Shall be as in Section 640 except:

Payment will be made under:

<u>ITEM NO.</u>	<u>ITEM</u>	<u>PAY UNIT</u>
640.2401----25	White Reflectorized Pavement Marking Paints, 6" x 15 mils	Linear Feet
640.2402----25	Yellow Reflectorized Pavement Marking Paints, 6" x 15 mils	Linear Feet
640.2403----25	White Reflectorized Pavement Letters	Each
640.2404----25	White Reflectorized Pavement Symbols	Each