

ITEM 621.5105--25 – CLEAN, GRADE AND SHAPE EXISTING ROADSIDE

1. DESCRIPTION:

- 1.01 This work shall consist of grading, compacting, trimming and disposing of existing material adjacent to shoulders in the locations indicated in the contract documents or as directed by the Engineer.

2. MATERIALS: NONE SPECIFIED

3. CONSTRUCTION DETAILS:

- 3.01 The Contractor shall grade and/or remove existing materials adjacent to the shoulders. The roadside shall be graded to drain to the lines and grades detailed in the contract documents or as directed by the Engineer.
- 3.02 After excess material has been trimmed, the area shall be compacted using methods and equipment approved by the Engineer.
- 3.03 The final, compacted surface of the roadside shall not extend above the shoulder and shall be less than 3/8" below the shoulder surface.
- 3.04 Excess material shall be disposed of in accordance with the provisions of subsection 203-3.08, Disposal of Surplus Excavated Materials.

4. METHOD OF MEASUREMENT

- 4.01 The work shall be measured as the number of feet measured along each outside edge of shoulder along which such work is performed. The Engineer will determine the areas where work is required, in advance of work operations.

5. BASIS OF PAYMENT

- 5.01 The unit price bid per foot shall include the cost of all labor, material and equipment necessary to satisfactorily complete the work.