

**ITEM 606.9003--25 - TRANSITION BETWEEN 42" HALF SECTION NJ SHAPE TO 34" HALF SECTION SINGLE SLOPE CONCRETE BARRIER**

**1. DESCRIPTION:**

- 1.01 Under this item, the Contractor shall construct and place a transition between 42" half section NJ shape concrete barrier to 34" half section single slope concrete barrier and component parts of the type and sizes illustrated on the plans at the locations shown in accordance with these specifications, and as directed by the Engineer.

**2. MATERIALS:**

- 2.01 Materials shall meet the requirements of Section 606-2 of the Standard Specifications.
- 2.02 **Disposal of Material:** The Contractor shall remove and dispose of milling and/or grinding slurry, by a method approved by the Engineer. The pavement shall be returned to a debris-free state prior to re-opening for traffic.

**3. CONSTRUCTION DETAILS:**

- 3.01 Transitions Constructed of, or with, Concrete shall be constructed at the locations indicated on the plans, in accordance with these specifications, the contract documents and the direction of the Engineer. The shapes illustrated in the plans shall be provided. The requirements of Subsection 606-3.19 of the Standard Specifications shall apply.

**4. METHOD OF MEASUREMENT:**

- 4.01 Transitions will be measured by the actual number of units installed in accordance with the plans, standard sheets and/or as directed by the Engineer.

**5. BASIS OF PAYMENT:**

- 5.01 The requirements of Subsection 606-5.12 Transition between Concrete Sections of the Standard Specifications shall apply. The unit price bid per concrete transition shall include the cost of all labor, equipment, and material necessary to satisfactorily complete the work, including back-up posts, connections and hardware and the Pay Unit shall be Each.