

ITEM 608.01010125 - WORK PAD

1. DESCRIPTION:

- 1.01 This work shall consist of construction and placement of a work pad in accordance with the plans and specifications or as ordered by the Engineer.

2. MATERIALS:

The Contractor shall have the option of using a Portland Cement Concrete (P.C.C.) or manufactured “plastic/fiberglass” material.

- 2.01 Material for P.C.C. work pads shall meet the requirements of Section 608-2 of the NYS DOT Standard Specifications.
- 2.02 Manufactured “plastic/fiberglass” materials shall be based on catalog cuts submitted to, and approved by the Engineer.

3. CONSTRUCTION DETAILS:

- 3.01 P.C.C. construction details shall meet the requirements of Section 608-3.01 of the NYSDOT Standard Specifications.
- 3.02 Work pad shall be installed on a level, compacted base, free of topsoil or other unsuitable materials. Top of work pad to be approximately flush with surrounding grade.
- 3.03 Work pad size shall be a minimum of four feet (4') x four feet (4') unless otherwise indicated on the Plans. P.C.C. pads shall be a minimum thickness of four inches (4").

4. METHOD OF MEASUREMENT:

- 4.01 This work shall be measured as the number of work pads installed in accordance with the plans, specifications and/or as ordered by the Engineer.

5. BASIS OF PAYMENT:

- 5.01 The unit price bid for each work pad shall include the cost of all labor, material and equipment, including excavation and disposal of unsuitable material, and fill material if needed, to complete the work to the satisfaction of the Engineer.