

**ITEM 203.0202--25 - ROADWAY REMOVAL**

**1. DESCRIPTION:**

- 1.01 The Contractor shall remove and dispose of existing pavement where indicated on the plans or as ordered by the Engineer.

**2. MATERIALS:**

- 2.01 Not specified.

**3. CONSTRUCTION DETAILS:**

- 3.01 The Contractor shall remove the pavement in a neat workmanlike manner by any suitable means that does not damage the adjacent pavement, curbing or existing underground utilities. Sawing to neat lines will be required only where adjacent pavement is to remain or where ordered by the Engineer. This work must conform to the details shown on the plans. The removed pavement shall be properly disposed of by the Contractor, as approved by the Engineer.

**4. METHOD OF MEASUREMENT:**

- 4.01 Roadway Removal shall be measured by the number of square yards of pavement removed and disposed of as shown on the plans or ordered by the Engineer.
- 4.02 Pavement is defined as the traveled way, including ramps, exclusive of shoulders and curbing. This item applies to all types of pavement whether they be Portland cement and concrete, asphalt concrete or a combination thereof. Where the roadway to be removed is bordered by curbs which are also designated for removal concurrent with the pavement, the Contractor may remove the curbs with the roadway pavement. Curb removal shall be paid for separately under the appropriate item. Subbase and shoulder removal, if called for on the plans, shall be paid for under the appropriate items.

**5. BASIS OF PAYMENT:**

- 5.01 The unit price bid per square yard for this item shall include the cost of furnishing all labor, materials, and equipment necessary to remove and dispose of the pavement, mesh reinforcement, transverse joints, and longitudinal ties except that saw cutting will be paid for under the appropriate item.