

**ITEM 619.1704--25 - CONCRETE BARRIER MARKER**

**1. DESCRIPTION:**

- 1.01 Under this item the Contractor shall furnish and install Concrete Barrier markers in accordance with the plans, specifications and as ordered by the Engineer.

**2. MATERIALS:**

- 2.01 A retro-reflective surface capable of reflecting incident light from wide angles shall be applied to the surface facing traffic. Silver color shall be used on the right side facing traffic and yellow on the left.

The following markers are approved for use under this specification:

Flexx 2020  
Duraflex Corporation  
297 Margaret King Avenue  
Ringwood, New Jersey 07456

Stimsonite Barrier Delineator 965  
Amerace Corporation  
Signal Products Division  
7542 North Natchez Avenue  
Niles, Illinois 60648

Portable Concrete Barrier Marker PCBM-12  
DAPCO  
Davidson Plastic Co.  
18726 East Valley Highway  
Kent, WA 98032

Or equal as approved by the New York State Thruway Authority.

**3. CONSTRUCTION DETAILS:**

- 3.01 The marker shall be attached to the concrete barrier 6 inches below the top, or as directed by the Engineer and spacing shall be as shown on the plans.
- 3.02 The marker shall be installed in accordance with the manufacturer's instructions. Bolting the marker to the concrete barrier may be allowed.

**4. METHOD OF MEASUREMENT:**

- 4.01 The number of markers to be paid for under this item will be the number of markers installed in accordance with these specifications or as directed by the Engineer.

**5. BASIS OF PAYMENT:**

- 5.01 The unit price bid for each marker shall include the cost of furnishing all labor, materials and equipment necessary to complete the work, and to maintain the markers.