

**ITEM 602.3564--25 - LINING 64 INCH ARCH PIPE WITH POLYESTER FORMED IN PLACE PIPE LINER**  
**ITEM 602.3572--25 - LINING 72 INCH ARCH PIPE WITH POLYESTER FORMED IN PLACE PIPE LINER**

**1. DESCRIPTION:**

- 1.01 This work shall consist of lining Arched Pipe with Polyester Formed in Place Pipe Liner in accordance with the Contract Documents and as directed by the Engineer. All provisions of Standard Specification Section 602 pertaining to Lining with Polyester Formed in Place Liner shall apply.

**2. MATERIALS:**

- 2.01 Material requirements are specified in §706-06 of the May 1, 2008 Standard Specifications.

**3. CONSTRUCTION DETAILS:**

- 3.01 Provide the Engineer with written details of how the work is to be progressed a minimum of ten (10) days prior to starting. Include pipe manufacturer's instructions, dewatering, assembly drawings, necessary insertion and bracing methods, and proposed shotcreting, concrete, and void filling methods.

**4. METHOD OF MEASUREMENT:**

- 4.01 This work will be measured as the number of linear feet along the bottom centerline, measured to the nearest foot of Lining with Polyester Formed in Place Pipe Liner satisfactorily installed.

**5. BASIS OF PAYMENT:**

- 5.01 The unit price bid shall include the cost of furnishing all labor, materials, and equipment necessary to satisfactorily complete the work.