



DETAIL 9.3.2(a)
COVER PLATE DETAIL
FOR MEDIAN CONCRETE BARRIER
NOT TO SCALE

LEGEND.

* - THE SIZE OF THREADED INSERTS AND ANCHOR BOLTS TO BE DETERMINED BY THE MANUFACTURER OF THE JOINT SYSTEM. APPLY ANTI-SEIZE LUBRICANT TO THREADS DURING INSTALLATION.

** - BLOCKOUT WIDTH IN BARRIER FOR JOINT HARDWARE

*** - BLOCKOUT HEIGHT IN BARRIER.

DETAIL 9.3.2(b)
COVER PLATE DETAIL
FOR CONCRETE BARRIER
HALF SECTION

DESIGN MOVEMENTS:

[REDACTED]

NOTES:

1. THE CONCRETE FURNISHED AND PLACED ON THE DECK IN THE AREA OF THE RECESSES FOR INSTALLING THE COVERPLATE SYSTEM SHALL COMPLY WITH THE SPECS FOR THE SLAB ITEM, EXCEPT THAT MACHINE FINISHING WILL NOT BE REQUIRED. THE COST FOR FURNISHING AND PLACING THIS CONCRETE SHALL BE INCLUDED IN THE UNIT PRICE OF THE SLAB ITEM.
2. THE COST FOR THE JOINT WORK ON THE CURB/SIDEWALK/BARRIER, INCLUDING THE COVERPLATE AND FASTENERS SHALL BE INCLUDED IN THE PRICE BID FOR THE CURB/SIDEWALK/BARRIER ITEM(S).