

TOLL LANE CLOSURE (INTERMEDIATE-TERM)

GENERAL:


THIS PLATE SHALL BE USED FOR CLOSURES EXCEEDING 6 HOURS BUT ARE LESS THAN 12 HOURS. IF THE WORK REQUIRES A CLOSURE THAT EXCEEDS 12 HOURS, A LONG-TERM TOLL LANE CLOSURE SHALL BE USED.

NOTES:

1. THE BARRIER VEHICLE SHALL HAVE HAZARD LIGHTS AND AMBER WARNING LIGHTS OPERATING.
2. THE ARROW PANEL MODE WILL DEPEND UPON THE AVAILABLE OPEN LANES IN THE PLAZA.
3. THREE STANDARD TRAFFIC CONES, OR A SINGLE DRUM, MAY BE PLACED BEHIND THE BARRIER VEHICLE.
4. THE RED "X" OVER THE LANE SHALL BE ACTIVATED. IN DEDICATED E-Z PASS LANES, THE FLASHING YELLOW BEACON SHALL BE TURNED OFF.
5. FOR OVERHEAD CANOPY SIGNS, THE FOLLOWING SHALL APPLY:
 - A. FIXED SIGNS MAY REMAIN UNCOVERED;
 - B. "DRUM" SIGNS SHALL DISPLAY "LANE CLOSED" (WHERE AVAILABLE) OR THE MIXED MODE PANEL;
 - C. "CLAMSHELL" SIGNS SHOULD BE CLOSED (FOLDED FROM VIEW);
 - D. LANES WITHOUT AN OVERHEAD CANOPY SIGN REQUIRE NO ADDITIONAL MEASURES.
6. IN REVERSIBLE LANES, ONE TRAFFIC CONE SHALL BE PLACED AT THE OPPOSITE END OF THE CLOSED LANE. A MIRRORRED CLOSURE AT OPPOSITE ENDS OF THE LANE SHOULD ALSO BE CONSIDERED.

LEGEND

- ▲ ▲ ▲ TRAFFIC CONES (OPTIONAL)
- ◀ ▶ ARROW PANEL
- ARROW PANEL SUPPORT OR TRAILER
- WORK VEHICLE
- BARRIER VEHICLE WITH ATTENUATOR
- ◆ ◆ WARNING FLAGS (OPTIONAL) MINIMUM



| | | |
|-------|---------------------------------------|-----------------|
| | TITLE OF DRAWING | |
| | TOLL LANE CLOSURE (INTERMEDIATE-TERM) | |
| DATE: | 4/09 | DRAWING NUMBER: |
| | | TLC-IT |