



GENERAL PLAN



SIZE	MEMBER											
	HORIZONTAL SIGN SUPPORT						VERTICAL SIGN SUPPORT					
	H1	H2	H3	H4	H5	H6	V1	V2	V3	V4	V5	V6
LENGTH (FT.)												
SPACING BETWEEN MEMBERS (FT.)												



ELEVATION



ELEVATION



PLAN VIEW
HORIZONTAL CROSS-BRACING

- * IF MIN. VERTICAL CLEARANCE TO BOTTOM FLANGE IS LESS THAN [REDACTED] THEN BOTTOM OF SIGN PANEL SHALL BE MOUNTED ABOVE THE BOTTOM FLANGE OF THE FASCIA BEAM OR GIRDER.
- ** PRIOR TO ANY INSTALLATION, SEE NOTE 1 OF INSTALLATION PROCEDURE.

DL - DIAPHRAGM TO LEFT OF STABILIZING COMPONENTS
DR - DIAPHRAGM TO RIGHT OF STABILIZING COMPONENTS

DIMENSION	
A	B

STRUCTURAL STEEL NOTES:

- 1). [REDACTED]
- 2). BOLT HOLES: [REDACTED]
- 3). COATINGS: [REDACTED]

BOLT, NUT, AND WASHER NOTES:

[REDACTED]

INSTALLATION PROCEDURE:

- REVIEW THIS RECOMMENDED PROCEDURE BEFORE INSTALLATION. VARIATIONS TO THIS PROCEDURE CAN BE CARRIED OUT. REGARDLESS, THE STABILIZING COMPONENTS MUST BE FULLY INSTALLED BEFORE THE WEIGHT OF THE HORIZONTAL SIGN SUPPORT OR VERTICAL SIGN SUPPORT IS APPLIED TO THE FASCIA BEAM OR GIRDER. ALL DAMAGED GALVANIZED COATINGS SHALL BE REPAIRED WITH ZINC MATERIAL. TACK WELDING OF ANY KIND IS NOT ALLOWED.
- 1). VERIFY INSTALLATION LOCATION SHOWN IN GENERAL PLAN. ADJUST ENTIRE SIGN STRUCTURE POSITION TO AVOID INDIVIDUAL SIGN SUPPORTS INTERFERING WITH EXISTING DIAPHRAGMS OR OTHER OBSTRUCTIONS.
 - 2). FIELD DRILL AND TEMPORARILY INSTALL FASCIA STABILIZING TEE.
 - 3). VERIFY REQUIRED SIGN CLEARANCE OVER ROADWAY, OR OTHER VERTICAL CONTROL POINT, AND FIELD DRILL VERTICAL SIGN SUPPORT.
 - 4). FIELD DRILL AND INSTALL INTERIOR STABILIZING TEE.
 - 5). FIELD DRILL AND INSTALL UPPER & LOWER STABILIZING ANGLES.
 - 6). SUPPORT FASCIA STABILIZING TEE (USING DRIFT PINS, ETC) AND REMOVE FASTENERS USED FOR TEMPORARY INSTALLATION IN STEP 2.
 - 7). INSTALL HORIZONTAL SIGN SUPPORT AND CROSS-BRACING (IF SPECIFIED) ALL FASTENERS SHALL BE FULLY TIGHTENED BEFORE THE WEIGHT OF THE SUPPORT IS APPLIED TO THE BRIDGE.
 - 8). INSTALL VERTICAL SIGN SUPPORT IF NOT ALREADY INSTALLED TO HORIZONTAL SIGN SUPPORT.
 - 9). REPEAT STEPS 2 THROUGH 8 FOR EACH SIGN SUPPORT.

DATE	DESCRIPTION	BY	SYM.
REVISIONS			
NEW YORK STATE THRUWAY AUTHORITY DEPARTMENT OF ENGINEERING SERVICES 200 SOUTHERN BLVD., ALBANY, N.Y. 12209			
TITLE OF PROJECT			
LOCATION OF PROJECT			
TITLE OF DRAWING			
SIGN STRUCTURE PLAN AND ELEVATION VIEWS			
		CONTRACT NUMBER:	
		*	
		DATE:	
		SEPT., 1994	
		DRAWING NUMBER:	
		EZ-1	